



## uEye UI-2210RE colour models, VGA (640x480)

The uEye RE 2210 colour models are equipped with a robust housing which meets in connection with the optional available lens tubes the protection classes IP65 and IP67. The fast and light-sensitive progressive scan 1/2" sensor achieves 75 frames per second in fullframe-mode. Binning or AOI offer more than 100 frames.

Included in delivery is the complete uEye software package:

The comfortable, easy to use uEye SDK

Standard drivers like Direct Show (WDM), Active X and TWAIN

Interfaces for popular machine vision software

The extensive uEye Demo and other specific demo-programs, which are all provided also in source code.

- 1/2" CCD sensor, global shutter, progressive scan
- max. 75 fps, 122 fps in AOI-mode with 320x240 pixels
- Exposure: 0,04 - 630 ms (freerun mode)
- AOI horizontal and vertical
- Asynchronous, universal trigger
- Digital out
- Binning vertical

### Available variants for this product:



AB.0010.1.189  
10.00


#### UI-2210RE-C

**CCD, colour, global shutter, progressive scan, 75 fps, standard IR-filter**

- Standard IR-filter
- Dimensions: 41x41x55,5mm (HxWxD)
- Weight: 180g





Call for Pricing

## Accessories for product "uEye UI-2210RE colour models, VGA (640x480)"

Product image	Item number	Description	Infos
	AD.0040.2.12200 .00	<b>USB 2.0 data cable 5 m – straight, IP65/67</b> <ul style="list-style-type: none"><li>■ shielded USB 2.0 cable</li><li>■ straight RE connector to USB-A</li></ul>	Call for Pricing



## Accessories for product "uEye UI-2210RE colour models, VGA (640x480)"

Product image	Item number	Description	Infos
	AD.0040.2.13400 .00	<b>USB 2.0 drag chain data cable 5 m – 90° angled, IP65/67</b> <ul style="list-style-type: none"><li>■ shielded USB 2.0 cable for use in a drag chain or robotic environment</li><li>■ angled RE connector to USB-A</li></ul>	Call for Pricing
	AD.0040.2.12600 .00	<b>USB 2.0 trigger/strobe cable 5 m, 90° angled, IP65/67</b> <ul style="list-style-type: none"><li>■ 90° angled RE connector to open ends</li></ul>	Call for Pricing
	AD.0040.2.13600 .00	<b>USB 2.0 drag chain data cable 8 m – IP65/67, straight</b> <ul style="list-style-type: none"><li>■ shielded cable beyond the standards of the USB Implementers Forum Inc.</li><li>■ for use in a drag chain or robotic environment</li><li>■ straight RE connector to USB-A</li></ul>	Call for Pricing
	SL.0028.2.06200 .00	<b>uEye RE four Port Hub</b> <ul style="list-style-type: none"><li>■ metal case for industrial use. IP 65 / IP67, Clamp for top hat rail mount</li><li>■ All connectors can be screwed</li></ul>	Call for Pricing